





PA-400 Series

The Palo Alto Networks PA-400 Series
Next-Generation Firewalls, comprising the
PA-410, PA-415, PA-440, PA-445, PA-450, and
PA-460, bring ML-Powered NGFW capabilities
to distributed enterprise branch offices, retail
locations, and midsize businesses.

The world's first ML-Powered Next-Generation Firewall enables you to prevent unknown threats, see, and secure everything—including the internet of things (IoT)—and reduce errors with automatic policy recommendations.

Highlights

- World's first ML-Powered NGFW
- Eleven-time Leader in the Gartner Magic Quadrant for Network Firewalls
- Leader in the Forrester Wave: Enterprise Firewalls, Q4 2022
- Spans a range of performance needs for the distributed enterprise with a broad lineup
- · Offers security in a desktop form factor
- Supports high availability with active/active and active/passive modes
- Delivers predictable performance with security services
- Features a silent, fanless design with an optional redundant power supply for branch and home offices
- Simplifies deployment of large numbers of firewalls with optional Zero Touch Provisioning (ZTP)
- Supports centralized administration with Panorama network security management
- Maximizes security investments and prevents business disruptions with AIOps

The controlling element of the PA-400 Series is PAN-OS, the same software that runs all Palo Alto Networks NGFWs. PAN-OS natively classifies all traffic, inclusive of applications, threats, and content, and then ties that traffic to the user regardless of location or device type. The application, content, and user—in other words, the elements that run your business—then serve as the basis of your security policies, resulting in improved security posture and reduced incident response times.

Key Security and Connectivity Features

ML-Powered Next-Generation Firewall

- Embeds machine learning (ML) in the core of the firewall to provide inline signatureless attack prevention for file-based attacks while identifying and immediately stopping never-before-seen phishing attempts.
- Leverages cloud-based ML processes to push zero-delay signatures and instructions back to the NGFW.
- Uses behavioral analysis to detect IoT devices and make policy recommendations as part of a cloud-delivered and natively integrated service on the NGFW.
- · Automates policy recommendations that save time and reduce the chance of human error.

Identifies and Categorizes All Applications, on All Ports, All the Time, with Full Layer 7 Inspection

- Identifies the applications traversing your network irrespective of port, protocol, evasive techniques, or encryption (TLS/SSL); in addition, automatically discovers and controls new applications to keep pace with the SaaS explosion with a SaaS Security subscription.
- Uses the application, not the port, as the basis for all your safe enablement policy decisions: allow, deny, schedule, inspect, and apply traffic-shaping.
- Offers the ability to create custom App-ID tags for proprietary applications or request App-ID development for new applications from Palo Alto Networks.
- Identifies all payload data within an application (e.g., files and data patterns) to block malicious files and thwart exfiltration attempts.
- Creates standard and customized application usage reports, including software-as-a-service (SaaS) reports that provide insight into all sanctioned and unsanctioned SaaS traffic on your network.
- Enables safe migration of legacy Layer 4 rule sets to App-ID-based rules with built-in Policy Optimizer, giving you a rule set that is more secure and easier to manage.

Check out the App-ID tech brief for more information.

Enforces Security for Users at Any Location, on Any Device, While Adapting Policy Based on User Activity

- Enables visibility, security policies, reporting, and forensics based on users and groups—not just IP addresses.
- Easily integrates with a wide range of repositories to leverage user information: wireless LAN controllers, VPNs, directory servers, SIEMs, proxies, and more.
- Allows you to define Dynamic User Groups (DUGs) on the firewall to take time-bound security actions without waiting for changes to be applied to user directories.
- Applies consistent policies irrespective of users' locations (office, home, travel, etc.) and devices (iOS and Android mobile devices; macOS, Windows, and Linux desktops and laptops; Citrix and Microsoft VDI; and terminal servers).
- Prevents corporate credentials from leaking to third-party websites and prevents reuse of stolen credentials by enabling multifactor authentication (MFA) at the network layer for any application without any application changes.
- · Provides dynamic security actions based on user behavior to restrict suspicious or malicious users.
- Consistently authenticates and authorizes your users, regardless of their location and where user identity stores live, to move quickly toward a Zero Trust security posture with Cloud Identity Engine—an entirely new cloud-based architecture for identity-based security.

Check out the Cloud Identity Engine solution brief for more information.



Prevents Malicious Activity Concealed in Encrypted Traffic

- Inspects and applies policy to TLS/SSL-encrypted traffic, both inbound and outbound, including for traffic that uses TLS 1.3 and HTTP/2.
- Offers rich visibility into TLS traffic, such as amount of encrypted traffic, TLS/SSL versions, cipher suites, and more, without decrypting.
- Enables control over use of legacy TLS protocols, insecure ciphers, and misconfigured certificates to mitigate risks.
- Facilitates easy deployment of decryption and lets you use built-in logs to troubleshoot issues, such as applications with pinned certificates.
- Lets you enable or disable decryption flexibly based on URL category, source and destination zone, address, user, user group, device, and port, for privacy and compliance purposes.
- Allows you to create a copy of decrypted traffic from the firewall (i.e., decryption mirroring) and send it to traffic collection tools for forensics, historical purposes, or data loss prevention (DLP).
- Allows you to intelligently forward all traffic (decrypted TLS, nondecrypted TLS, and non-TLS) to third-party security tools with Network Packet Broker, optimize your network performance, and reduce operating expenses.

Refer to this decryption whitepaper to learn where, when, and how to decrypt to prevent threats and secure your business.

Offers Centralized Management and Visibility

- Benefits from centralized management, configuration, and visibility for multiple distributed Palo Alto Networks NGFWs (irrespective of location or scale) through Panorama network security management, in one unified user interface.
- Streamlines configuration sharing through Panorama with templates and device groups and scales log
 collection as logging needs increase. PA-410, PA-415, PA-440, PA-445, PA-450, and PA-460 allow
 export session logs to Panorama and Cortex Data Lake. PA-415, PA-440, PA-445, PA-450, and PA-460
 also support on box session logging.
- Enables users, through the Application Command Center (ACC), to obtain deep visibility and comprehensive insights into network traffic and threats.

Maximize Your Security Investment and Prevent Business Disruption with AIOps

- AIOps for NGFW delivers continuous best practice recommendations customized to your unique deployment to strengthen your security posture and get the most out of your security investment.
- Intelligently predicts firewall health, performance, and capacity problems based on ML powered by advanced telemetry data. It also provides actionable insights to resolve the predicted disruptions.

Detect and Prevent Advanced Threats with Cloud-Delivered Security Services

Today's sophisticated cyberattacks can spawn 45,000 variants in 30 minutes using multiple threat vectors and advanced techniques to deliver malicious payloads. Traditional siloed security causes challenges for organizations by introducing security gaps, increasing overhead for security teams, and hindering business productivity with inconsistent access and visibility.

Seamlessly integrated with our industry-leading NGFWs, our Cloud-Delivered Security Services use the network effect of 80,000 customers to instantly coordinate intelligence and protect against all threats across all vectors. Eliminate coverage gaps across your locations and take advantage of best-in-class security delivered consistently in a platform to stay safe from even the most advanced and evasive threats.

- Advanced Threat Prevention: Stop known exploits, malware, spyware, and command-and-control
 (C2) threats while utilizing industry-first prevention of zero-day attacks—prevent 60% more
 unknown injection attacks and 48% more highly evasive command-and-control traffic than
 traditional IPS solutions.
- Advanced WildFire: Ensure files are safe by automatically preventing known, unknown, and highly evasive malware 60X faster with the industry's largest threat intelligence and malware prevention engine.
- Advanced URL Filtering: Ensure safe access to the internet and prevent 40% more web-based attacks with the industry's first real-time prevention of known and unknown threats, stopping 88% of malicious URLs at least 48 hours before other vendors.
- **DNS Security:** Gain 40% more threat coverage and stop 85% of malware that abuses DNS for command and control and data theft without requiring changes to your infrastructure.



- Enterprise DLP: Minimize risk of a data breach, stop out-of-policy data transfers, and enable compliance consistently across your enterprise with 2x greater coverage of any cloud-delivered enterprise DLP.
- SaaS Security: Stay ahead of the SaaS explosion with the industry's only Next-Generation CASB to automatically see and secure all apps across all protocols.
- **IoT Security:** Safeguard every "thing" and implement Zero Trust device security 20x faster with the industry's smartest security for smart devices.

Enables SD-WAN Functionality

- · Allows you to easily adopt SD-WAN by simply enabling it on your existing firewalls.
- · Enables you to safely implement SD-WAN, which is natively integrated with our industry-leading security.
- · Delivers an exceptional end-user experience by minimizing latency, jitter, and packet loss.

Delivers a Unique Approach to Packet Processing with Single-Pass Architecture

- Performs networking, policy lookup, application and decoding, and signature matching—for all threats and content—in a single pass. This significantly reduces the amount of processing overhead required to perform multiple functions in one security device.
- Avoids introducing latency by scanning traffic for all signatures in a single pass, using streambased, uniform signature matching.
- Enables consistent and predictable performance when security subscriptions are enabled. (In table 1, "Threat Prevention throughput" is measured with multiple subscriptions enabled.)

Table 1: PA-400 Series Performance and Capacities						
	PA-410	PA-415	PA-440	PA-445	PA-450	PA-460
Firewall throughput (HTTP/appmix)*	1.59/1.1	1.65/1.2 Gbps	2.8/2.2 Gbps	2.8/2.2 Gbps	3.5/2.9 Gbps	5.1/4.4 Gbps
Threat Prevention throughput (HTTP/appmix)†	0.6/0.68 Gbps	0.6/0.69 Gbps	1.0/1.0 Gbps	1.0/1.0 Gbps	1.4/1.6 Gbps	2.1/2.4 Gbps
IPsec VPN throughput [†]	0.92 Gbps	0.92 Gbps	1.6 Gbps	1.6 Gbps	2.2 Gbps	3.0 Gbps
Max concurrent sessions [§]	64,000	64,000	200,000	200,000	300,000	400,000
New sessions per second	12,000	12,000	37,500	37,500	51,000	73,000
Virtual systems (base/max)#	1/1	1/1	1/2	1/2	1/5	1/5

Note: Results were measured on PAN-OS 11.0.

- * Firewall throughput is measured with App-ID and logging enabled, utilizing 64 KB HTTP/appmix transactions.
- † Threat Prevention throughput is measured with App-ID, IPS, antivirus, antispyware, WildFire, DNS Security, file blocking, and logging enabled, utilizing 64 KB HTTP/appmix transactions.
- ‡ IPsec VPN throughput is measured with 64 KB HTTP transactions and logging enabled.
- § Max concurrent sessions are measured utilizing HTTP transactions.
- $\mid\mid$ New sessions per second is measured with application override, utilizing 1 byte HTTP transactions.
- # Adding virtual systems over base quantity requires a separately purchased license and at minimum PAN-OS 11.0.

# Adding virtual systems over base quantity requires a separately purchased license and at minimum PAN-OS 11.0.				
Table 2: PA-400 Series Networking Features				
Interface Modes				
L2, L3, tap, virtual wire (transparent mode)				
Routing				
OSPFv2/v3 with graceful restart, BGP with graceful restart, RIP, static routing				
Policy-based forwarding				
Point-to-Point Protocol over Ethernet (PPPoE)				
Multicast: PIM-SM, PIM-SSM, IGMP v1, v2, and v3				
SD-WAN				
Path quality measurement (jitter, packet loss, latency)				
Initial path selection (PBF)				
Dynamic path change				

Table 2: PA-400 Series Networking Features (continued)

IPV6

L2, L3, tap, virtual wire (transparent mode)

Features: App-ID, User-ID, Content-ID, WildFire, and SSL decryption

SLAAC

IPsec and SSL VPN

Key exchange: manual key, IKEv1 and IKEv2 (pre-shared key, certificate-based authentication)

Encryption: 3des, AES (128-bit, 192-bit, 256-bit)

Authentication: MD5, SHA-1, SHA-256, SHA-384, SHA-512

GlobalProtect Large Scale VPN for simplified configuration and management*

Secure access over IPsec and SSL VPN tunnels using GlobalProtect gateway and portals*

VLANS

802.1Q VLAN tags per device/per interface: 4,094/4,094

Aggregate interfaces (802.3ad), LACP

* Requires GlobalProtect license.

Table 3: PA-400 Series Hardware Specifications

1/0

PA-410: RJ45 (7)

PA-440, PA-450, PA-460: RJ45 (8)

PA-415, PA-445: 1G SFP/RJ45 combo (1), RJ45 (4), RJ45/PoE (4)

Management I/O

PA-410: 10/100/1000 out-of-band management port (1), RJ45 console port (1), USB port (2)

PA-415, PA-445 SFP/RJ45(1 GB) combo management port (1), RJ45 console port (1), USB port (2), Micro USB console port (1)

PA-440, PA-450, PA-460: 10/100/1000 out-of-band management port (1), RJ45 console port (1), USB port (2), Micro USB console port (1)

Power Over Ethernet (PoE)

PA-415, PA-445 PoE RJ45 ports (4)

Total PoE Power Budget: 91 W

Maximum loading on single port: 60 W

Storage Capacity

PA-410: 64 GB eMMC

PA-415, PA-440, PA-445, PA-450, PA-460: 128 GB eMMC

Power Supply (Avg/Max Power Consumption)

PA-410: 17/18 W

PA-415, PA-440, PA-445: 29/34 W

PA-450, PA-460: 33/41 W

Max BTU/hi

PA-410: 78

PA-415, PA-440, PA-445: 117

PA-450, PA-460: 141

Input Voltage (Input Frequency)

100-240 VAC (50-60 Hz)

Max Current Consumption

PA-410: 1.5 A @ 12 VDC

PA-415, PA-440, PA-445: 2.9 A @ 12 VDC

PA-450, PA-460: 3.4 A @ 12 VDC



Table 3: PA-400 Series Hardware Specifications (continued)

Max Inrush Current

PA-410: 2.1 A

PA-415, PA-440, PA-445: 3.3 A

PA-450, PA-460: 4.2 A

Dimensions

PA-410: 1.63" H x 6.42" D x 9.53" W PA-415: 1.73" H x 13" D x 9" W PA-445: 1.66" H x 13" D x 8.87" W

PA-440, PA-450, PA-460: 1.74" H x 8.83" D x 8.07" W

Weight (Standalone Device/As Shipped)

PA-410: 3.1 lbs/5.9 lbs PA-415: 7.85 lbs/12.2 lbs PA-445: 8.7 lbs/12.6 lbs

PA-440, PA-450, PA-460: 5.0 lbs/7.8 lbs

Safety

cTUVus, CB

FMI

FCC Class B, CE Class B, VCCI Class B

Certifications

See paloaltonetworks.com/company/certifications.html

Environment

Operating temperature: 32°F to 104°F, 0°C to 40°C Nonoperating temperature: -4°F to 158°F, -20°C to 70°C

Passive cooling



3000 Tannery Way Santa Clara, CA 95054

Main: +1.408.753.4000 Sales: +1.866.320.4788 Support: +1.866.898.9087

www.paloaltonetworks.com

© 2023 Palo Alto Networks, Inc. Palo Alto Networks and the Palo Alto Networks logo are registered trademarks of Palo Alto Networks, Inc. A list of our trademarks can be found at https://www.paloaltonetworks.com/company/trademarks.html. All other marks mentioned herein may be trademarks of their respective companies. strata_ds_pa-400-series_071923